



## **PowerWalker DC SecureAdapter 12V**

12V DC UPS System

25W/2.1A DC UPS

Output Coaxial DC Connector

LED Indicators for UPS status

2.6Ah (2600mAh) Lithium-Ion Battery

Perfect solution for routers, access points, VoIP, IP cameras, Security Systems, Alarms, Modems, Decoders, etc



Item-No. 10120431

## **Product Features**

PowerWalker DC SecureAdapter is universal solution for small electronics. Replace your 12VDC adapter with our UPS and secure your devices from power outages. It can prevent disconnection during business video calls or data synchronising, it will keep essentials of your business operating but may also protect your property or health supporting all necessary monitoring devices. Typical applications are:

- Routers and switches,
- Signal amplifiers and repeaters,
- POE systems,
- Access points,
- security systems,
- smart home control panels,
- VoIP phones,
- IP cameras,
  - modems,
  - decoders,
  - Media players,
  - medical monitors

and many other 12VDC max 25W devices.

The UPS is equipped with 1m long cable and its compact size allows fitting it between other plugs in an extension cord. 12VDC is a global standard and 25W output on coaxial DC connector (OD 5.5mm / ID 2.5mm) will be compatible with most of your devices. High quality Samsung Lithium-Ion battery provides 3h backup time for typical router.









## **Technical Details**

## **Product Features**

Input	
Nominal Input Voltage	230VAC
Acceptable Input Voltage Range	90-264VAC
Acceptable Input Frequency Range	50Hz / 60Hz
Surge Protection	1.5kV
Output	
Output Power (max.)	25W/2.1A
Output Voltage	12VDC +/-5%
Battery	
Туре	3.7VDC / 2.6Ah (2600mAh) Lithium-ion
Recharge Time	3h for 90% without load after
(internal Battery)	complete discharge
Protection	
Battery	Deep Discharge, Over-charge and Short Circuit Protection
Input/Output	Fuse for Short-circuit and overload protection
Indicators	
Full Battery	Green lighting
Charging	Green flashing
Discharging	Green quick flashing
Fault	Red lighting

oaxial DC Connector D 5.5mm / ID 2.5mm m long cable 8 x 42 x 74 mm (WxHxD)
m long cable
8 x 42 x 74 mm (WxHxD)
8 x 42 x 74 mm (WxHxD)
lack
2kg
owerWalker DC SecureAdapter 12V
owerWalker DC SecureAdapter
2V, manual
N
N
13 x 52 x 104 mm (WxLxH)
21kg
6
70 x 390 x 225 mm (WxLxH)
7kg
0
0120431
260074977943
4 Months

Connections

